



## ADRIA L2A

---

LED-5L06E300ZL11/093/L100 NL 4K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ADRIA L2A

Product code: ADR50556

Type: LED-5L06E300ZL11/093/L100 NL 4K#

Short description of the luminaire: Stainless steel polished | pendant LED light ON/OFF | TRIPLEX OPAL hand blown glass shade | steel wire pendant ( with supply cable) 100 cm |



## Technical data


Types of luminaires	Classic on/off
Mounting type	Suspended - wire
Base material	stainless steel steel
Shade material	three-layer glass TRIPLEX OPAL
Base color	polished stainless steel
Shade color	white
Holding the shade	steel holder
Mounting location	ceiling
Width	250 mm
Length	250 mm
Height	250 mm
Diameter	ø 250 mm
Suspension length	1000 mm
mounting holes (diameter)	none
Energy Class	D
Impact strength	IK01
Operating temperature	from -20°C to +30°C

## Electrical data

Power consumption	14 W
Ingress Protection	IP40
Socket	LED modul
terminal block	none
Automatic circuit breaker type B10A	72 pcs
Automatic circuit breaker type B16A	116 pcs
Automatic circuit breaker type C10A	72 pcs
Automatic circuit breaker type C16A	116 pcs
Number of LED drivers	1

## Luminous data

Lum. flux of luminaire	2090 lm
Lum. flux of light source	2380 lm
Luminaire efficacy	149 lm/W
Chromaticity temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



Eulum data for calculation programs are available at

OSMONT, s.r.o.  
HYBRÁLEC 129,  
586 01 JIHLAVA, CZ

Logistical data

EAN	8591728202477
Warranty*	60 months

*\*The warranty for the batteries is valid for 36 months from the date of purchase.*

Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20208	093	white	