



ADRIA S1A

LED-1L77E500ZS11/090/L100 NB 3K#

WWW.OSMONT.CZ

ADRIA S1A

Product code: ADR50448

Type: LED-1L77E500ZS11/090/L100 NB 3K#

Short description of the luminaire: Stainless steel brushed | pendant LED light ON/OFF | TRIPLEX OPAL hand blown glass shade | cable pendant (with inner support wire) 100 cm |



Technical data


Types of luminaires	Classic on/off
Mounting type	Suspended - cable
Base material	stainless steel steel
Shade material	three-layer glass TRIPLEX OPAL
Base color	brushed stainless steel
Shade color	white
Holding the shade	steel holder
Mounting location	ceiling
Width	106 mm
Height	106 mm
Diameter	ø 106 mm
Suspension length	1000 mm
mounting holes (diameter)	none
Energy Class	D
Impact strength	IK01
Operating temperature	from -20°C to +30°C

Electrical data

Power consumption	3 W
Ingress Protection	IP40
Socket	LED modul
terminal block	none
Automatic circuit breaker type B10A	45 pcs
Automatic circuit breaker type B16A	72 pcs
Automatic circuit breaker type C10A	72 pcs
Automatic circuit breaker type C16A	115 pcs
Number of LED drivers	1

Luminous data

Lum. flux of luminaire	440 lm
Lum. flux of light source	500 lm
Luminaire efficacy	146 lm/W
Chromaticity temperature	3000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



Eulum data for calculation programs are available at www.osmont.cz.

TECHNICAL SHEET



Logistical data

EAN	8591728201708
Warranty*	60 months

**The warranty for the batteries is valid for 36 months from the date of purchase.*

Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20145	090		