



## AURA 5

---

LED-1L16E500K86/082 3/4K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# AURA 5

Product code: AUR71120


Type: LED-1L16E500K86/082 3/4K#

Short description of the luminaire: White surface-mounted changeable LED light ON/OFF with TRIPLEX OPAL glass shade



## Technical

Types of luminaires	Classic on/off
Mounting type	surface mounted
Base material	steel
Shade material	three-layer glass TRIPLEX OPAL
Base color	white Ral9003
Shade color	white
Holding the shade	folding system
Mounting location	ceiling/wall
Width	490 mm
Length	490 mm
Height	140 mm
Diameter	ø 490 mm
mounting holes (diameter)	4xø5mm
Installation wire (diameter)	2xø16mm
Energy Class	D
Impact strength	IK01
Operating temperature	from -20°C to +30°C




## Electric

Power consumption	24 W
Ingress Protection	IP43
Socket	LED modul
terminal block	snap terminal block
Automatic circuit breaker type B10A	37 pcs
Automatic circuit breaker type B16A	59 pcs
Automatic circuit breaker type C10A	37 pcs
Automatic circuit breaker type C16A	59 pcs

## Luminous

Lum. flux of luminaire	2590/2700 lm
Lum. flux of light source	3750/3910 lm
Luminaire efficacy	107 lm/W
Temperature	3000/4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0





Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).



## Additional assortment:

## Decorative collar

Product code	Name	Color	Description	Picture	Drawing
30134	K86/DL15	brushed stainless steel	the collar is held by the base		
30133	K86/DL14	polished stainless steel	the collar is held by the base		
30132	K86/DL4	white Ral9003	the collar is held by the base		

## Lampshade

Product code	Name	Color	Description	Picture	Drawing
20005	082	white		