



DELIA 3

LED-1L20E1050KN94/PC24 HF CORR 3/35/4K##


WWW.OSMONT.CZ

DELIA 3

Product code: DEL71507

Type: LED-1L20E1050KN94/PC24 HF CORR 3/35/4K##

Short description of the luminaire: White colour | ceiling or wall LED light with CORRIDOR function (DALI+HF sensor) | opal polycarbonate shade (PC)|



Technical data



Types of luminaires	Corridor
Mounting type	surface mounted
Base material	steel
Shade material	opal polycarbonate
Base color	white Ral9003
Shade color	white
Holding the shade	folding system
Mounting location	ceiling/wall
Width	500 mm
Length	500 mm
Height	85 mm
Diameter	ø 500 mm
mounting holes (diameter)	3xø5mm
Cable entrance	2xø16mm
Energy Class	D
Impact strength	IK10
Operating temperature	from -20°C to +30°C

Electrical data

Power consumption	48 W
Ingress Protection	IP54
Socket	LED modul
Sensor	HF
terminal block	snap terminal block
Automatic circuit breaker type B10A	14 pcs
Automatic circuit breaker type B16A	22 pcs
Automatic circuit breaker type C10A	23 pcs
Automatic circuit breaker type C16A	37 pcs
Switching current	22,5 A / 176 µsec
Number of LED drivers	1

Luminous data


Lum. flux of luminaire	5110/5330 lm
Lum. flux of light source	7740/8070 lm
Luminaire efficacy	106 lm/W
Chromaticity temperature	3000/3500/4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



www.osmont.cz
osmont@osmont.cz
(+420) 567 210 023
02.09.2026

EAN	8591728242374
Weight NtTO	3 Kg
Weight BtTO	3.4 Kg
Number of cartons	1 pcs
Package volume	0.023 m ³
Package 1 width	0.5 m
Package 1 length	0.5 m
Package 1 height	0.09 m
Warranty*	60 months

Installation dimensions:



Additional assortment:

Base for surface mounting

Product code	Name	Color	Picture	Drawing
33503	KN9,K9/BP 2-1 B	white Ral9003		

Lampshade

Product code	Name	Color	Picture	Drawing
20524	PC24	white		