



DELIA 3

LED-1L20E700KN94/PM24 HF CORR 3/35/4K##


WWW.OSMONT.CZ

DELIA 3

Product code: DEL71513

Type: LED-1L20E700KN94/PM24 HF CORR 3/35/4K##

Short description of the luminaire: White colour | ceiling or wall LED light with CORRIDOR function (DALI+HF sensor) | PMMA shade



Technical data



Types of luminaires	Corridor
Mounting type	surface mounted
Base material	steel
Shade material	opal polymethyl methacrylate
Base color	white Ral9003
Shade color	white
Holding the shade	folding system
Mounting location	ceiling/wall
Width	500 mm
Length	500 mm
Height	85 mm
Diameter	ø 500 mm
mounting holes (diameter)	3xø5mm
Cable entrance	2xø16mm
Energy Class	D
Impact strength	IK04
Operating temperature	from -20°C to +30°C

Electrical data

Power consumption	32 W
Ingress Protection	IP54
Socket	LED modul
Sensor	HF
terminal block	snap terminal block
Automatic circuit breaker type B10A	23 pcs
Automatic circuit breaker type B16A	37 pcs
Automatic circuit breaker type C10A	38 pcs
Automatic circuit breaker type C16A	62 pcs
Switching current	19 A / 288 µsec
Number of LED drivers	1

Luminous data

Lum. flux of luminaire	3520/3670 lm
Lum. flux of light source	5330/5560 lm
Luminaire efficacy	110 lm/W
Chromaticity temperature	3000/3500/4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



www.osmont.cz
osmont@osmont.cz
(+420) 567 210 023
29.07.2026

EAN	8591728242244
Weight NTO	2.95 Kg
Weight BTO	3.4 Kg
Number of cartons	1 pcs
Package volume	0.023 m ³
Package 1 width	0.51 m
Package 1 length	0.51 m
Package 1 height	0.09 m
Warranty*	60 months

Installation dimensions:

