



## DELIA CV1

---

LED-1L14EMP700KNV62/PC22C/NK1W HF 3K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# DELIA CV1

Product code: DEL69329



Type: LED-1L14EMP700KNV62/PC22C/NK1W HF 3K#

Short description of the luminaire: White colour | semi-recessed LED light with emergency backup combined and HF sensor | multipower driver | opal polycarbonate shade (PC) with black decorative stripe|



## Technical

Types of luminaires	Emergency combined + sensor
Mounting type	semi-recessed
Base material	steel
Shade material	opal polycarbonate
Base color	white Ral9003
Shade color	white - black
Holding the shade	folding system
Mounting location	ceiling/wall
Width	300 mm
Length	300 mm
Height	60 mm
Diameter	ø 300 mm
mounting holes (diameter)	none
Cable entrance	2xø16mm
Energy Class	D
Impact strength	IK10
Operating temperature	from -20°C to +30°C




## Electric

Power consumption	18 W
Ingress Protection	IP44
Socket	LED modul
Sensor	HF
Battery type	NiCd
Emergency time	3 hours
SELFTEST	no
terminal block	snap terminal block
Automatic circuit breaker type B10A	26 pcs
Automatic circuit breaker type B16A	40 pcs
Automatic circuit breaker type C10A	30 pcs
Automatic circuit breaker type C16A	48 pcs

## Luminous

Lum. flux of luminaire	1480 lm
Lum. flux of light source	2690 lm
Lum. flux of light source in emergency mode	150 lm
Luminaire efficacy	82 lm/W
Temperature	3000 K
Rated life time LED L80/B10	100000 hours



## TECHNICAL SHEET



CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

*Eulum data for calculation programs are available at  
www.osmont.cz.*

### Multipower

Possibility of output adjustment by the user (DIP switch on the current source).


I [mA]	700	600	500	400	
[%]	100	86	71	57	

### Logistic


EAN	8591728077341
Weight NTTO	1.75 Kg
Weight BTTO	1.95 Kg
Number of cartons	1 pcs
Package volume	0.017 m <sup>3</sup>
Package 1 width	0.31 m
Package 1 length	0.31 m
Package 1 height	0.18 m
Warranty*	60 months

*\*The warranty for the batteries is valid for 12 months from the date of purchase.*


### Installation dimensions:



Svítlidlo nesmí být z horní strany zakryto izolací.  
Luminaire must not be covered with insulating matting.



Rozměry dutiny pro vestavné svítlidlo [mm]:  
Dimensions of cavity for recessed luminaire [mm]:



## Additional assortment:

## Lampshade

Product code	Name	Color	Description	Picture	Drawing
20566	PC22C	white - black	příslušenství	