



ERIS CV2

LED-1L14EMP700KV64/412C HF 3K#


WWW.OSMONT.CZ

ERIS CV2

Product code: ERI67129



Type: LED-1L14EMP700KV64/412C HF 3K#

Short description of the luminaire: White semi-recessed LED light with sensor with TRIPLEX OPAL glass shade with black decorative stripe.



Technical

| | |
|------------------------------|--------------------------------|
| Types of luminaires | Sensor |
| Mounting type | semi-recessed |
| Base material | steel |
| Shade material | three-layer glass TRIPLEX OPAL |
| Base color | white Ral9003 |
| Shade color | white - black |
| Holding the shade | folding system |
| Mounting location | ceiling/wall |
| Width | 340 mm |
| Length | 340 mm |
| Height | 100 mm |
| Diameter | ø 340 mm |
| mounting holes (diameter) | none |
| Installation wire (diameter) | 2xØ16mm |
| Energy Class | D |
| Impact strength | IK01 |
| Operating temperature | from -20°C to +30°C |




Electric

| | |
|-------------------------------------|---------------------|
| Power consumption | 18 W |
| Ingress Protection | IP44 |
| Socket | LED modul |
| Sensor | HF |
| terminal block | snap terminal block |
| Automatic circuit breaker type B10A | 37 pcs |
| Automatic circuit breaker type B16A | 59 pcs |
| Automatic circuit breaker type C10A | 37 pcs |
| Automatic circuit breaker type C16A | 59 pcs |

Luminous

| | |
|-----------------------------|--------------|
| Lum. flux of luminaire | 1350 lm |
| Lum. flux of light source | 2690 lm |
| Luminaire efficacy | 75 lm/W |
| Temperature | 3000 K |
| Rated life time LED L80/B10 | 100000 hours |
| CRI | Ra80 |
| MacAdam | 3 |
| Blue light hazard | Risk group 0 |



Eulum data for calculation programs are available at

Multipower

Possibility of output adjustment by the user (DIP switch on the current source).


| | | | | | |
|--------|-----|-----|-----|-----|--|
| I [mA] | 700 | 600 | 500 | 400 | |
| [%] | 100 | 86 | 71 | 57 | |

Logistic


| | |
|-------------------|----------------------|
| EAN | 8591728099619 |
| Weight NTTO | 3.4 Kg |
| Weight BTTO | 3.7 Kg |
| Number of cartons | 1 pcs |
| Package volume | 0.034 m ³ |
| Package 1 width | 0.382 m |
| Package 1 length | 0.382 m |
| Package 1 height | 0.234 m |
| Warranty* | 60 months |

*The warranty for the batteries is valid for 12 months from the date of purchase.



Installation dimensions:



Světlo nesmí být z horní strany zakryto izolací.
Luminaire must not be covered with insulating matting.



Rozměry dutiny pro vestavné světlo [mm]:
Dimensions of cavity for recessed luminaire [mm]:



Montáž do pevných materiálů - sádkarton, dřevo.
Mounting into solid materials - plasterboard, wood.



Additional assortment:

Lampshade

| Product code | Name | Color | Description | Picture | Drawing |
|--------------|------|---------------|-------------|--|---------|
| 20131 | 412C | white - black | |  | |