



## ISIS L3A PM

LED-5L06E550ZL11/PM3A/L100 NK3HST C 4K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS L3A PM

Product code: ISI74707

Type: LED-5L06E550ZL11/PM3A/L100 NK3HST C 4K#

Short description of the luminaire: Black colour | pendant LED light with emergency backup combined ( with Self-test) | PMMA shade | steel wire pendant ( with supply cable) 100 cm |



## Technical data



Types of luminaires	Emergency combined SELFTEST
Mounting type	Suspended - wire
Base material	steel
Shade material	opal polymethyl methacrylate
Base color	black Ral9005
Shade color	white
Holding the shade	steel holder
Mounting location	ceiling
Width	350 mm
Length	350 mm
Height	350 mm
Diameter	ø 350 mm
Suspension length	1000 mm
mounting holes (diameter)	none
Energy Class	D
Impact strength	IK06
Operating temperature	from +5°C to +30°C

## Electrical data

Power consumption	26 W
Ingress Protection	IP40
Socket	LED modul
Battery type	LiFePO4
Emergency time	3 hours
SELFTEST	yes
terminal block	none
Automatic circuit breaker type B10A	15 pcs
Automatic circuit breaker type B16A	25 pcs
Automatic circuit breaker type C10A	31 pcs
Automatic circuit breaker type C16A	48 pcs
Number of LED drivers	1

## Luminous data

Lum. flux of luminaire	3750 lm
Lum. flux of light source	4260 lm
Lum. flux of light source in emergency mode	200 lm
Luminaire efficacy	144 lm/W
Chromaticity temperature	4000 K
Rated life time LED L80/B10	100000 hours



## TECHNICAL SHEET



CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

*Eulum data for calculation programs are available at  
www.osmont.cz.*

## Logistical data

EAN	8591728220631
Warranty*	60 months

*\*The warranty for the batteries is valid for 36 months from the date of purchase.*

## Additional assortment:

### Lampshade

Product code	Name	Color	Picture	Drawing
20726	PM3A (400mm)	white	