



## ISIS P3 PE

---

LED-5L06E600Z11/PE3/a1/NK1W MS 4K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS P3 PE

Product code: ISI68860

Type: LED-5L06E600Z11/PE3/a1/NK1W MS 4K#

Short description of the luminaire: Brass pendant LED light with emergency unit combined and polyethylene shade.



## Technical

|                              |                    |
|------------------------------|--------------------|
| Types of luminaires          | Emergency combined |
| Mounting type                | Suspended - rod    |
| Base material                | brass              |
| Shade material               | polyethylene       |
| Base color                   | polished brass     |
| Shade color                  | white              |
| Holding the shade            | folding system     |
| Mounting location            | ceiling            |
| Width                        | 400 mm             |
| Length                       | 400 mm             |
| Height                       | 400 mm             |
| Diameter                     | ø 400 mm           |
| Hinge length                 | 200 mm             |
| mounting holes (diameter)    | none               |
| Installation wire (diameter) | none               |
| Energy Class                 | D                  |
| Impact strength              | IK10               |
| Operating temperature        | from 0°C to +30°C  |



## Electric

|                                     |           |
|-------------------------------------|-----------|
| Power consumption                   | 27 W      |
| Ingress Protection                  | IP40      |
| Socket                              | LED modul |
| Battery type                        | LiFePO4   |
| Emergency time                      | 1 hours   |
| terminal block                      | none      |
| Automatic circuit breaker type B10A | 23 pcs    |
| Automatic circuit breaker type B16A | 36 pcs    |
| Automatic circuit breaker type C10A | 40 pcs    |
| Automatic circuit breaker type C16A | 64 pcs    |

## Luminous

|   |              |
|---|--------------|
| Lum. flux of luminaire                      | 4070 lm      |
| Lum. flux of light source                   | 4630 lm      |
| Lum. flux of light source in emergency mode | 170 lm       |
| Luminaire efficacy                          | 150 lm/W     |
| Temperature                                 | 4000 K       |
| Rated life time LED L80/B10                 | 100000 hours |
| CRI   | Ra80         |
| MacAdam                                     | 3            |
| Blue light hazard                           | Risk group 0 |



## TECHNICAL SHEET



Eulum data for calculation programs are available at  
[www.osmont.cz](http://www.osmont.cz).

### Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728038571        |
| Weight NTTO       | 3.2 Kg               |
| Weight BTTO       | 4.3 Kg               |
| Number of cartons | 2 pcs                |
| Package volume    | 0.081 m <sup>3</sup> |
| Package 1 width   | 0.405 m              |
| Package 1 length  | 0.405 m              |
| Package 1 height  | 0.41 m               |
| Warranty*         | 60 months            |

\*The warranty for the batteries is valid for 12 months from the date of purchase.

### Additional assortment:

#### Lampshade

| Product code | Name | Color | Description | Picture  | Drawing |
|--------------|------|-------|-------------|--|---------|
| 20530        | PE3  | white |             |  |         |