



ISIS P3A PM

LED-5L06E550Z11/PM3A/L40 NB 3K#

WWW.OSMONT.CZ

ISIS P3A PM

Product code: ISI74081

Type: LED-5L06E550Z11/PM3A/L40 NB 3K#

Short description of the luminaire: Stainless steel brushed | pendant LED light ON/OFF | PMMA shade | rod pendant 40 cm |



Technical data

Types of luminaires	Classic on/off
Mounting type	Suspended - rod
Base material	stainless steel steel
Shade material	opal polymethyl methacrylate
Base color	brushed stainless steel
Shade color	white
Holding the shade	steel holder
Mounting location	ceiling
Width	350 mm
Length	350 mm
Height	350 mm
Diameter	ø 350 mm
Suspension length	400 mm
mounting holes (diameter)	none
Energy Class	D
Impact strength	IK06
Operating temperature	from -20°C to +30°C


Electrical data

Power consumption	26 W
Ingress Protection	IP40
Socket	LED modul
terminal block	none
Automatic circuit breaker type B10A	31 pcs
Automatic circuit breaker type B16A	50 pcs
Automatic circuit breaker type C10A	52 pcs
Automatic circuit breaker type C16A	85 pcs
Number of LED drivers	1

Luminous data

Lum. flux of luminaire	3590 lm
Lum. flux of light source	4080 lm
Luminaire efficacy	138 lm/W
Chromaticity temperature	3000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at www.osmont.cz.



TECHNICAL SHEET



Logistical data

EAN	8591728214562
Warranty*	60 months

**The warranty for the batteries is valid for 36 months from the date of purchase.*

Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20726	PM3A (350mm)	white		