



## ISIS P4 PE

---

LED-5L07E900Z11/PE4/a1 B DALI 4K##

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS P4 PE

Product code: ISI66605

Type: LED-5L07E900Z11/PE4/a1 B DALI 4K##

Short description of the luminaire: White colour | pendant LED light DALI | polyethylene shade | rod pendant 20 cm |



## Technical


|                           |                     |
|---------------------------|---------------------|
| Types of luminaires       | Dimmable            |
| Mounting type             | Suspended - rod     |
| Base material             | steel               |
| Shade material            | polyethylene        |
| Base color                | white Ra9003        |
| Shade color               | white               |
| Holding the shade         | folding system      |
| Mounting location         | ceiling             |
| Width                     | 500 mm              |
| Length                    | 500 mm              |
| Height                    | 500 mm              |
| Diameter                  | ø 500 mm            |
| Hinge length              | 200 mm              |
| mounting holes (diameter) | none                |
| Cable entrance            | none                |
| Energy Class              | D                   |
| Impact strength           | IK10                |
| Operating temperature     | from -20°C to +30°C |

## Electric

|                                     |           |
|-------------------------------------|-----------|
| Power consumption                   | 41 W      |
| Ingress Protection                  | IP40      |
| Socket                              | LED modul |
| terminal block                      | none      |
| Automatic circuit breaker type B10A | 14 pcs    |
| Automatic circuit breaker type B16A | 23 pcs    |
| Automatic circuit breaker type C10A | 23 pcs    |
| Automatic circuit breaker type C16A | 38 pcs    |

## Luminous

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 6120 lm      |
| Lum. flux of light source   | 6960 lm      |
| Luminaire efficacy          | 149 lm/W     |
| Temperature                 | 4000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |



Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).


Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728037017        |
| Weight NTTO       | 4.4 Kg               |
| Weight BTTO       | 6.3 Kg               |
| Number of cartons | 2 pcs                |
| Package volume    | 0.157 m <sup>3</sup> |
| Package 1 width   | 0.52 m               |
| Package 1 length  | 0.52 m               |
| Package 1 height  | 0.53 m               |
| Warranty*         | 60 months            |

*\*The warranty for the batteries is valid for 12 months from the date of purchase.*

Additional assortment:

Lampshade

| Product code | Name | Color | Description   | Picture  | Drawing |
|--------------|------|-------|---------------|--|---------|
| 20531        | PE4  | white | příslušenství |  |         |