



ISIS P5 PM

LED-5L07E1050Z11/PM5/a1 MS DALI 4K##

WWW.OSMONT.CZ

ISIS P5 PM

Product code: ISI60525


Type: LED-5L07E1050Z11/PM5/a1 MS DALI 4K##

Short description of the luminaire: Brass polished finish | pendant LED light | dimmable DALI | PMMA shade



Technical

Types of luminaires	Dimmable
Mounting type	Suspended - rod
Base material	brass
Shade material	glossy polymethyl methacrylate
Base color	polished brass
Shade color	white
Holding the shade	steel holder
Mounting location	ceiling
Width	600 mm
Length	600 mm
Height	600 mm
Diameter	ø 600 mm
Hinge length	200 mm
mounting holes (diameter)	none
Installation wire (diameter)	none
Energy Class	D
Impact strength	IK06
Operating temperature	from -20°C to +30°C



Electric

Power consumption	48 W
Ingress Protection	IP40
Socket	LED modul
terminal block	none
Automatic circuit breaker type B10A	14 pcs
Automatic circuit breaker type B16A	23 pcs
Automatic circuit breaker type C10A	23 pcs
Automatic circuit breaker type C16A	38 pcs

Luminous

Lum. flux of luminaire	7100 lm
Lum. flux of light source	8070 lm
Luminaire efficacy	147 lm/W
Temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



Eulum data for calculation programs are available at www.osmont.cz.

TECHNICAL SHEET



Logistic

EAN	8591728014872
Weight NTTO	5.2 Kg
Weight BTTO	7.8 Kg
Number of cartons	2 pcs
Package volume	0.278 m ³
Package 1 width	0.62 m
Package 1 length	0.62 m
Package 1 height	0.63 m
Warranty*	60 months

**The warranty for the batteries is valid for 12 months from the date of purchase.*

Additional assortment:

Lampshade

Product code	Name	Color	Description	Picture	Drawing
20666	PM5	white			