



## ISIS P5 PM

---

LED-5L07E1050Z11/PM5/a3 NB DALI 4K##

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS P5 PM

Product code: ISI60547

Type: LED-5L07E1050Z11/PM5/a3 NB DALI 4K##

Short description of the luminaire: Stainless brushed finish | pendant LED light | dimmable DALI | PMMA shade



## Technical

|                              |                                |
|------------------------------|--------------------------------|
| Types of luminaires          | Dimmable                       |
| Mounting type                | Suspended - rod                |
| Base material                | stainless steel steel          |
| Shade material               | glossy polymethyl methacrylate |
| Base color                   | brushed stainless steel        |
| Shade color                  | white                          |
| Holding the shade            | steel holder                   |
| Mounting location            | ceiling                        |
| Width                        | 600 mm                         |
| Length                       | 600 mm                         |
| Height                       | 600 mm                         |
| Diameter                     | ø 600 mm                       |
| Hinge length                 | 600 mm                         |
| mounting holes (diameter)    | none                           |
| Installation wire (diameter) | none                           |
| Energy Class                 | D                              |
| Impact strength              | IK06                           |
| Operating temperature        | from -20°C to +30°C            |


## Electric

|                                     |           |
|-------------------------------------|-----------|
| Power consumption                   | 48 W      |
| Ingress Protection                  | IP40      |
| Socket                              | LED modul |
| terminal block                      | none      |
| Automatic circuit breaker type B10A | 14 pcs    |
| Automatic circuit breaker type B16A | 23 pcs    |
| Automatic circuit breaker type C10A | 23 pcs    |
| Automatic circuit breaker type C16A | 38 pcs    |

## Luminous

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 7100 lm      |
| Lum. flux of light source   | 8070 lm      |
| Luminaire efficacy          | 147 lm/W     |
| Temperature                 | 4000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |

Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).



## TECHNICAL SHEET



### Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728015091        |
| Weight NTTO       | 5.4 Kg               |
| Weight BTTO       | 8 Kg                 |
| Number of cartons | 2 pcs                |
| Package volume    | 0.278 m <sup>3</sup> |
| Package 1 width   | 0.62 m               |
| Package 1 length  | 0.62 m               |
| Package 1 height  | 0.63 m               |
| Warranty*         | 60 months            |

*\*The warranty for the batteries is valid for 12 months from the date of purchase.*

### Additional assortment:

#### Lampshade

| Product code | Name | Color | Description | Picture | Drawing |
|--------------|------|-------|-------------|---------|---------|
| 20666        | PM5  | white |             |         |         |