



ISIS P5 PM-M

LED-5L07E1050Z11/PM5M/a3 B 4K##

WWW.OSMONT.CZ

ISIS P5 PM-M

Product code: ISI60642

Type: LED-5L07E1050Z11/PM5M/a3 B 4K##

Short description of the luminaire: White color | pendant LED light | ON/OFF | PMMA matt shade



Technical

| | |
|------------------------------|------------------------------|
| Types of luminaires | Classic on/off |
| Mounting type | Suspended - rod |
| Base material | steel |
| Shade material | opal polymethyl methacrylate |
| Base color | white Ra9003 |
| Shade color | white |
| Holding the shade | steel holder |
| Mounting location | ceiling |
| Width | 600 mm |
| Length | 600 mm |
| Height | 600 mm |
| Diameter | ø 600 mm |
| Hinge length | 600 mm |
| mounting holes (diameter) | none |
| Installation wire (diameter) | none |
| Energy Class | D |
| Impact strength | IK06 |
| Operating temperature | from -20°C to +30°C |


Electric

| | |
|--------------------|-----------|
| Power consumption | 48 W |
| Ingress Protection | IP40 |
| Socket | LED modul |
| terminal block | none |

Luminous

| | |
|-----------------------------|--------------|
| Lum. flux of luminaire | 7100 lm |
| Lum. flux of light source | 8070 lm |
| Luminaire efficacy | 147 lm/W |
| Temperature | 4000 K |
| Rated life time LED L80/B10 | 100000 hours |
| CRI | Ra80 |
| MacAdam | 3 |
| Blue light hazard | Risk group 0 |

Eulum data for calculation programs are available at www.osmont.cz.




Logistic

| | |
|-------------------|----------------------|
| EAN | 8591728016043 |
| Weight NTTO | 5.4 Kg |
| Weight BTTO | 8 Kg |
| Number of cartons | 2 pcs |
| Package volume | 0.278 m ³ |
| Package 1 width | 0.62 m |
| Package 1 length | 0.62 m |
| Package 1 height | 0.63 m |
| Warranty* | 60 months |

**The warranty for the batteries is valid for 12 months from the date of purchase.*

Additional assortment:

Lampshade

| Product code | Name | Color | Description | Picture | Drawing |
|--------------|-------|-------|-------------|--|---------|
| 20667 | PM5-M | white | |  | |