



## KRUGER 2 FOP

Private: LED-1L16EMP700KN83/FOP2B NK3HST 3K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# KRUGER 2 FOP

Product code: KRU60254

Type: Private: LED-1L16EMP700KN83/FOP2B NK3HST 3K#




## Technical

Types of luminaires	Emergency combined
Mounting type	surface mounted
Base material	steel
Shade material	Plastic opal prismatic (FOP) with metal collar
Shade color	white
Holding the shade	folding system
Mounting location	ceiling/wall
Width	395 mm
Length	395 mm
Height	80 mm
mounting holes (diameter)	3xØ5mm
Installation wire (diameter)	2xØ16mm
Impact strength	IKxx



## Electric


Power consumption	34 W
Ingress Protection	IP40
Socket	LED modul
Battery type	LiFePO4
Emergency time	3 hours
terminal block	snap terminal block



## Luminous

Lum. flux of luminaire	3080 lm
Lum. flux of light source	5050 lm
Lum. flux of light source in emergency mode	200 lm
Temperature	3000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).



TECHNICAL SHEET



Logistic

EAN	8591728157487
Number of cartons	1 pcs

*\*The warranty for the batteries is valid for 12 months from the date of purchase.*

Installation dimensions:

