

KRUGER 2 FOP


Private: LED-1L16EMP700KN83/FOP2C NK3HST HF 4K#

WWW.OSMONT.CZ

KRUGER 2 FOP

Product code: KRU60763

Type: Private: LED-1L16EMP700KN83/FOP2C NK3HST HF 4K#




Technical

Types of luminaires	Emergency combined + sensor
Mounting type	surface mounted
Base material	steel
Shade material	Plastic opal prismatic (FOP) with metal collar
Shade color	white - black
Holding the shade	folding system
Mounting location	ceiling/wall
Width	395 mm
Length	395 mm
Height	80 mm
mounting holes (diameter)	3xØ5mm
Installation wire (diameter)	2xØ16mm
Impact strength	IKxx




Electric

Power consumption	34 W
Ingress Protection	IP40
Socket	LED modul
Battery type	LiFePO4
Emergency time	3 hours
terminal block	snap terminal block



Luminous

Lum. flux of luminaire	2850 lm
Lum. flux of light source	5270 lm
Lum. flux of light source in emergency mode	200 lm
Temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



Eulum data for calculation programs are available at www.osmont.cz.

TECHNICAL SHEET



Logistic

EAN	8591728158217
Number of cartons	1 pcs

**The warranty for the batteries is valid for 12 months from the date of purchase.*

Installation dimensions:

