



ZETA 2 UP/DOWN

LED-3L651E950/350K2H/FP92 B 2/1 4K##

WWW.OSMONT.CZ

ZETA 2 UP/DOWN

Product code: ZET60622


Type: LED-3L651E950/350K2H/FP92 B 2/1 4K##

Short description of the luminaire: White colour | ceiling or wall LED light ON/OFF | multipower driver | direct and indirect lighting | matt PMMA shade



Technical data

Types of luminaires	Classic on/off
Mounting type	surface mounted
Base material	steel
Shade material	opal polymethyl methacrylate
Base color	white Ral9003
Shade color	white
Mounting location	ceiling/wall
Width	600 mm
Length	600 mm
Height	105 mm
Diameter	ø 600 mm
mounting holes (diameter)	3xø5mm
Cable entrance	2xø16mm
Energy Class	D
Operating temperature	from -20°C to +30°C



Electrical data

Power consumption	38+14 W
Ingress Protection	IP40
Socket	LED modul
terminal block	snap terminal block

Luminous data

Lum. flux of luminaire	4700+1620 lm
Lum. flux of light source	6520+2380 lm
Chromaticity temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at www.osmont.cz.




Logistical data

EAN	8591728234539
Weight NTTO	5.5 Kg
Weight BTTO	6.3 Kg
Number of cartons	1 pcs
Warranty*	60 months

*The warranty for the batteries is valid for 36 months from the date of purchase.

Installation dimensions:



Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20669	PM92	white		