



ZETA ST2 UP/DOWN

LED-3L651E950/350ZST/FP92/L100 C DALI 4K##

WWW.OSMONT.CZ

ZETA ST2 UP/DOWN

Product code: ZET60673

Type: LED-3L651E950/350ZST/FP92/L100 C DALI 4K##

Short description of the luminaire: Black colour | pendant LED light DALI| direct and indirect lighting version | matt PMMA shade | textile cable pendant (with inner support wire) 100 cm |



Technical data





Types of luminaires	Dimmable
Mounting type	Suspended - cable
Base material	steel
Shade material	opal polymethyl methacrylate
Base color	black Ral9005
Shade color	white
Mounting location	ceiling
Width	600 mm
Length	600 mm
Height	50 mm
Diameter	ø 600 mm
Suspension length	1000 mm
mounting holes (diameter)	3xø5mm
Cable entrance	2xø16mm
Energy Class	B
Operating temperature	from -20°C to +30°C

Electrical data

Power consumption	52 W
Ingress Protection	IP40
Socket	LED modul
terminal block	snap terminal block
Automatic circuit breaker type B10A	15 pcs
Automatic circuit breaker type B16A	25 pcs
Automatic circuit breaker type C10A	26 pcs
Automatic circuit breaker type C16A	42 pcs
Number of LED drivers	2

Luminous data

Lum. flux of luminaire	6320 lm
Lum. flux of light source	8900 lm
Luminaire efficacy	121 lm/W
Chromaticity temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



cd/klm — C0 - C180 — C90 - C270 $\eta = 100\%$

Eulum data for calculation programs are available at www.osmont.cz.

Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20669	PM92	white		