



## ADRIA P1A

---

LED-1L77E500Z11/090/L60 B 4K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ADRIA P1A

Product code: ADR50921

Type: LED-1L77E500Z11/090/L60 B 4K#

Short description of the luminaire: White colour | pendant LED light ON/OFF | TRIPLEX OPAL hand blown glass shade| rod pendant 60 cm |



## Technical data

|                           |                                |
|---------------------------|--------------------------------|
| Types of luminaires       | Classic on/off                 |
| Mounting type             | Suspended - rod                |
| Base material             | steel                          |
| Shade material            | three-layer glass TRIPLEX OPAL |
| Base color                | white Ral9003                  |
| Shade color               | white                          |
| Holding the shade         | steel holder                   |
| Mounting location         | ceiling                        |
| Width                     | 106 mm                         |
| Length                    | 106 mm                         |
| Height                    | 106 mm                         |
| Diameter                  | ø 106 mm                       |
| Suspension length         | 600 mm                         |
| mounting holes (diameter) | none                           |
| Energy Class              | D                              |
| Impact strength           | IK01                           |
| Operating temperature     | from -20°C to +30°C            |


## Electrical data

|                    |           |
|--------------------|-----------|
| Power consumption  | 3 W       |
| Ingress Protection | IP40      |
| Socket             | LED modul |
| terminal block     | none      |

## Luminous data

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 460 lm       |
| Lum. flux of light source   | 520 lm       |
| Chromaticity temperature    | 4000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |

Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).



## TECHNICAL SHEET



### Logistical data

|           |               |
|-----------|---------------|
| EAN       | 8591728207861 |
| Warranty* | 60 months     |

*\*The warranty for the batteries is valid for 36 months from the date of purchase.*

### Additional assortment:

#### Lampshade

| Product code | Name | Color | Picture   | Drawing |
|--------------|------|-------|---|---------|
| 20145        | 090  |       |  |         |