



ADRIA P1A

LED-1L77E500Z11/090/L100 NL 4K#

WWW.OSMONT.CZ

ADRIA P1A

Product code: ADR50938

Type: LED-1L77E500Z11/090/L100 NL 4K#

Short description of the luminaire: Stainless steel polished | pendant LED light ON/OFF | TRIPLEX OPAL hand blown glass shade | rod pendant 100 cm |



Technical data

| | |
|---------------------------|--------------------------------|
| Types of luminaires | Classic on/off |
| Mounting type | Suspended - rod |
| Base material | stainless steel steel |
| Shade material | three-layer glass TRIPLEX OPAL |
| Base color | polished stainless steel |
| Shade color | white |
| Holding the shade | steel holder |
| Mounting location | ceiling |
| Width | 106 mm |
| Length | 106 mm |
| Height | 106 mm |
| Diameter | ø 106 mm |
| Suspension length | 1000 mm |
| mounting holes (diameter) | none |
| Energy Class | D |
| Impact strength | IK01 |
| Operating temperature | from -20°C to +30°C |



Electrical data

| | |
|--------------------|-----------|
| Power consumption | 3 W |
| Ingress Protection | IP40 |
| Socket | LED modul |
| terminal block | none |

Luminous data

| | |
|-----------------------------|--------------|
| Lum. flux of luminaire | 460 lm |
| Lum. flux of light source | 520 lm |
| Chromaticity temperature | 4000 K |
| Rated life time LED L80/B10 | 100000 hours |
| CRI | Ra80 |
| MacAdam | 3 |
| Blue light hazard | Risk group 0 |

Eulum data for calculation programs are available at www.osmont.cz.



TECHNICAL SHEET



Logistical data

| | |
|-----------|---------------|
| EAN | 8591728208035 |
| Warranty* | 60 months |

**The warranty for the batteries is valid for 36 months from the date of purchase.*

Additional assortment:

Lampshade

| Product code | Name | Color | Picture | Drawing |
|--------------|------|-------|---|---------|
| 20145 | 090 | |  | |