



## ADRIA P3

---

LED-5L06E600Z11/096/a3/NK1W NB 3K#


[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ADRIA P3

Product code: ADR68322


Type: LED-5L06E600Z11/096/a3/NK1W NB 3K#

Short description of the luminaire: Stainless brushed pendant LED light with emergency unit combined with TRIPLEX OPAL glass shade.



## Technical

|                              |                                |
|------------------------------|--------------------------------|
| Types of luminaires          | Emergency combined             |
| Mounting type                | Suspended - rod                |
| Base material                | stainless steel steel          |
| Shade material               | three-layer glass TRIPLEX OPAL |
| Base color                   | brushed stainless steel        |
| Shade color                  | white                          |
| Holding the shade            | folding system                 |
| Mounting location            | ceiling                        |
| Width                        | 400 mm                         |
| Length                       | 400 mm                         |
| Height                       | 400 mm                         |
| Diameter                     | ø 400 mm                       |
| Hinge length                 | 600 mm                         |
| mounting holes (diameter)    | none                           |
| Installation wire (diameter) | none                           |
| Energy Class                 | D                              |
| Impact strength              | IK01                           |
| Operating temperature        | from 0°C to +30°C              |




## Electric

|                                     |           |
|-------------------------------------|-----------|
| Power consumption                   | 27 W      |
| Ingress Protection                  | IP40      |
| Socket                              | LED modul |
| Battery type                        | LiFePO4   |
| Emergency time                      | 1 hours   |
| terminal block                      | none      |
| Automatic circuit breaker type B10A | 23 pcs    |
| Automatic circuit breaker type B16A | 36 pcs    |
| Automatic circuit breaker type C10A | 40 pcs    |
| Automatic circuit breaker type C16A | 64 pcs    |

## Luminous

|   |              |
|---|--------------|
| Lum. flux of luminaire                      | 3910 lm      |
| Lum. flux of light source                   | 4440 lm      |
| Lum. flux of light source in emergency mode | 170 lm       |
| Luminaire efficacy                          | 144 lm/W     |
| Temperature                                 | 3000 K       |
| Rated life time LED L80/B10                 | 100000 hours |
| CRI   | Ra80         |



## TECHNICAL SHEET



|                   |              |
|-------------------|--------------|
| MacAdam           | 3            |
| Blue light hazard | Risk group 0 |

*Eulum data for calculation programs are available at  
www.osmont.cz.*


### Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728060565        |
| Weight NTTO       | 6.1 Kg               |
| Weight BTTO       | 7.2 Kg               |
| Number of cartons | 2 pcs                |
| Package volume    | 0.081 m <sup>3</sup> |
| Package 1 width   | 0.405 m              |
| Package 1 length  | 0.405 m              |
| Package 1 height  | 0.41 m               |
| Warranty*         | 60 months            |

*\*The warranty for the batteries is valid for 12 months from the date of purchase.*

### Additional assortment:

#### Lampshade

| Product code | Name | Color | Description | Picture   | Drawing |
|--------------|------|-------|-------------|---|---------|
| 20040        | 096  | white |             |  |         |