



## ADRIA P3A HP

LED-5L06E900Z11/097/L80 NK3H NB 3K#


[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ADRIA P3A HP

Product code: ADR50332

Type: LED-5L06E900Z11/097/L80 NK3H NB 3K#

Short description of the luminaire: Stainless steel brushed | pendant high-power LED light with emergency backup combined | TRIPLEX OPAL hand blown glass shade | rod pendant 80 cm |



## Technical data

|                           |                                |
|---------------------------|--------------------------------|
| Types of luminaires       | Emergency combined             |
| Mounting type             | Suspended - rod                |
| Base material             | stainless steel steel          |
| Shade material            | three-layer glass TRIPLEX OPAL |
| Base color                | brushed stainless steel        |
| Shade color               | white                          |
| Holding the shade         | steel holder                   |
| Mounting location         | ceiling                        |
| Width                     | 350 mm                         |
| Length                    | 350 mm                         |
| Height                    | 350 mm                         |
| Diameter                  | Ø 350 mm                       |
| Suspension length         | 800 mm                         |
| mounting holes (diameter) | none                           |
| Energy Class              | D                              |
| Impact strength           | IK01                           |
| Operating temperature     | from -20°C to +30°C            |

## Electrical data

|                    |           |
|--------------------|-----------|
| Power consumption  | 43 W      |
| Ingress Protection | IP40      |
| Socket             | LED modul |
| Battery type       | LiFePO4   |
| Emergency time     | 3 hours   |
| terminal block     | none      |

## Luminous data

|   |              |
|---|--------------|
| Lum. flux of luminaire                      | 5630 lm      |
| Lum. flux of light source                   | 6400 lm      |
| Lum. flux of light source in emergency mode | 200 lm       |
| Chromaticity temperature                    | 3000 K       |
| Rated life time LED L80/B10                 | 100000 hours |
| CRI   | Ra80         |
| MacAdam                                     | 3            |
| Blue light hazard                           | Risk group 0 |

Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).



TECHNICAL SHEET



Logistical data

|           |               |
|-----------|---------------|
| EAN       | 8591728198985 |
| Warranty* | 60 months     |

\*The warranty for the batteries is valid for 36 months from the date of purchase.

Installation dimensions:



## Additional assortment:

## Lampshade

| Product code | Name | Color | Picture   | Drawing |
|--------------|------|-------|---|---------|
| 20144        | 097  | white |  |         |