



## ADRIA S4 HP

LED-5L08E950ZS11/098/L100 NB DALI 3K##


[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ADRIA S4 HP

Product code: ADR62229

Type: LED-5L08E950ZS11/098/L100 NB DALI 3K##

Short description of the luminaire: Stainless steel brushed | pendant high-power LED light DALI | TRIPLEX OPAL hand blown glass shade| cable pendant ( with inner support wire) 100 cm |



## Technical

|                           |                                |
|---------------------------|--------------------------------|
| Types of luminaires       | Dimmable                       |
| Mounting type             | Suspended - cable              |
| Base material             | stainless steel steel          |
| Shade material            | three-layer glass TRIPLEX OPAL |
| Base color                | brushed stainless steel        |
| Shade color               | white                          |
| Holding the shade         | steel holder                   |
| Mounting location         | ceiling                        |
| Width                     | 500 mm                         |
| Length                    | 500 mm                         |
| Height                    | 500 mm                         |
| Diameter                  | Ø 500 mm                       |
| Hinge length              | 1000 mm                        |
| mounting holes (diameter) | 3xØ5mm                         |
| Cable entrance            | 2xØ16mm                        |
| Energy Class              | D                              |
| Impact strength           | IK01                           |
| Operating temperature     | from -20°C to +30°C            |

## Electric

|                                     |                     |
|-------------------------------------|---------------------|
| Power consumption                   | 59 W                |
| Ingress Protection                  | IP40                |
| Socket                              | LED modul           |
| terminal block                      | snap terminal block |
| Automatic circuit breaker type B10A | 15 pcs              |
| Automatic circuit breaker type B16A | 25 pcs              |
| Automatic circuit breaker type C10A | 26 pcs              |
| Automatic circuit breaker type C16A | 42 pcs              |

## Luminous

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 8100 lm      |
| Lum. flux of light source   | 9200 lm      |
| Luminaire efficacy          | 137 lm/W     |
| Temperature                 | 3000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |



Eulum data for calculation programs are available at

Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728058135        |
| Weight NTTO       | 5.8 Kg               |
| Weight BTTO       | 7.32 Kg              |
| Number of cartons | 2 pcs                |
| Package volume    | 0.148 m <sup>3</sup> |
| Package 1 width   | 0.52 m               |
| Package 1 length  | 0.52 m               |
| Package 1 height  | 0.53 m               |
| Warranty*         | 60 months            |

\*The warranty for the batteries is valid for 12 months from the date of purchase.

Installation dimensions:



## Additional assortment:

## Lampshade

| Product code | Name | Color | Description   | Picture   | Drawing |
|--------------|------|-------|---------------|---|---------|
| 20041        | 098  | white | příslušenství |  |         |