



## CARINA V2

---

LED-1L20E700KNV96/426 3K##


[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# CARINA V2

Product code: CAR67170



Type: LED-1L20E700KNV96/426 3K##

Short description of the luminaire: White semi-recessed LED light ON/OFF with TRIPLEX OPAL glass shade.



## Technical

|                              |                                |
|------------------------------|--------------------------------|
| Types of luminaires          | Classic on/off                 |
| Mounting type                | semi-recessed                  |
| Base material                | steel                          |
| Shade material               | three-layer glass TRIPLEX OPAL |
| Base color                   | white Ral9003                  |
| Shade color                  | white                          |
| Holding the shade            | folding system                 |
| Mounting location            | ceiling/wall                   |
| Width                        | 500 mm                         |
| Length                       | 500 mm                         |
| Height                       | 40 mm                          |
| Diameter                     | ø 500 mm                       |
| mounting holes (diameter)    | none                           |
| Installation wire (diameter) | none                           |
| Energy Class                 | D                              |
| Impact strength              | IK01                           |
| Operating temperature        | from -20°C to +30°C            |




## Electric

|                                     |           |
|-------------------------------------|-----------|
| Power consumption                   | 32 W      |
| Ingress Protection                  | IP44      |
| Socket                              | LED modul |
| terminal block                      | none      |
| Automatic circuit breaker type B10A | 55 pcs    |
| Automatic circuit breaker type B16A | 85 pcs    |
| Automatic circuit breaker type C10A | 55 pcs    |
| Automatic circuit breaker type C16A | 85 pcs    |

## Luminous

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 3460 lm      |
| Lum. flux of light source   | 5330 lm      |
| Luminaire efficacy          | 108 lm/W     |
| Temperature                 | 3000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |




Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).

Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728010621        |
| Weight NTTO       | 4.9 Kg               |
| Weight BTTO       | 5.4 Kg               |
| Number of cartons | 1 pcs                |
| Package volume    | 0.037 m <sup>3</sup> |
| Package 1 width   | 0.5 m                |
| Package 1 length  | 0.53 m               |
| Package 1 height  | 0.14 m               |
| Warranty*         | 60 months            |


\*The warranty for the batteries is valid for 12 months from the date of purchase.

Installation dimensions:



## Additional assortment:

## Lampshade

| Product code | Name | Color | Description | Picture  | Drawing |
|--------------|------|-------|-------------|--|---------|
| 20116        | 426  | white |             |  |         |