



ELSA 3 IP

LED-1L15E350BD14/027 HF 3/4K#


WWW.OSMONT.CZ

ELSA 3 IP

Product code: ELS71225


Type: LED-1L15E350BD14/027 HF 3/4K#

Short description of the luminaire: White surface-mounted changeable LED light with sensor with TRIPLEX OPAL glass shade



Technical

| | |
|------------------------------|--------------------------------|
| Types of luminaires | Sensor |
| Mounting type | surface mounted |
| Base material | polypropylene composite |
| Shade material | three-layer glass TRIPLEX OPAL |
| Base color | white Ral9003 |
| Shade color | white |
| Holding the shade | bayonet |
| Mounting location | ceiling/wall |
| Width | 360 mm |
| Length | 360 mm |
| Height | 94 mm |
| Diameter | ø 360 mm |
| mounting holes (diameter) | 3xø5mm |
| Installation wire (diameter) | 2xø16mm |
| Energy Class | D |
| Impact strength | IK01 |
| Operating temperature | from -20°C to +30°C |




Electric

| | |
|-------------------------------------|---------------------|
| Power consumption | 13 W |
| Ingress Protection | IP65 |
| Socket | LED modul |
| Sensor | HF |
| terminal block | snap terminal block |
| Automatic circuit breaker type B10A | 65 pcs |
| Automatic circuit breaker type B16A | 105 pcs |
| Automatic circuit breaker type C10A | 39 pcs |
| Automatic circuit breaker type C16A | 63 pcs |

Luminous

| | |
|-----------------------------|--------------|
| Lum. flux of luminaire | 1490/1550 lm |
| Lum. flux of light source | 2130/2220 lm |
| Luminaire efficacy | 114 lm/W |
| Temperature | 3000/4000 K |
| Rated life time LED L80/B10 | 100000 hours |
| CRI | Ra80 |
| MacAdam | 3 |
| Blue light hazard | Risk group 0 |



Eulum data for calculation programs are available at www.osmont.cz.

Logistic

| | |
|-------------------|----------------------|
| EAN | 8591728098100 |
| Weight NTTO | 3.1 Kg |
| Weight BTTO | 3.4 Kg |
| Number of cartons | 1 pcs |
| Package volume | 0.016 m ³ |
| Package 1 width | 0.375 m |
| Package 1 length | 0.355 m |
| Package 1 height | 0.12 m |
| Warranty* | 60 months |

*The warranty for the batteries is valid for 12 months from the date of purchase.

Installation dimensions:




Additional assortment:

Decorative collar

| Product code | Name | Color | Description | Picture | Drawing |
|--------------|---------|--------------------------|---------------------------------|--|---------|
| 30136 | B14/X14 | polished stainless steel | the collar is held by the shade |  | |
| 30135 | B14/X4 | white Ral9003 | the collar is held by the shade |  | |
| 30138 | B14/X13 | grey | the collar is held by the shade |  | |
| 30137 | B14/X12 | polished brass | the collar is held by the shade |  | |

Lampshade

| Product code | Name | Color | Description | Picture | Drawing |
|--------------|------|-------|-------------|--|---------|
| 20082 | 027 | white | |  | |