



## ELSA V4

---

LED-1L16ET500BTV15/029 DALI 27-65K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ELSA V4

Product code: ELS63094


Type: LED-1L16ET500BTV15/029 DALI 27-65K#

Short description of the luminaire: White semi-recessed LED light with Tunable White system with TRIPLEX OPAL glass shade.



## Technical

|                              |                                |
|------------------------------|--------------------------------|
| Types of luminaires          | Tunable White                  |
| Mounting type                | semi-recessed                  |
| Base material                | steel                          |
| Shade material               | three-layer glass TRIPLEX OPAL |
| Base color                   | white Ral9003                  |
| Shade color                  | white                          |
| Holding the shade            | bayonet                        |
| Mounting location            | ceiling/wall                   |
| Width                        | 420 mm                         |
| Length                       | 420 mm                         |
| Height                       | 69 mm                          |
| Diameter                     | ø 420 mm                       |
| mounting holes (diameter)    | none                           |
| Installation wire (diameter) | 2xØ16mm                        |
| Energy Class                 | D                              |
| Impact strength              | IK01                           |
| Operating temperature        | from -20°C to +30°C            |




## Electric

|                                     |                     |
|-------------------------------------|---------------------|
| Power consumption                   | 23 W                |
| Ingress Protection                  | IP44                |
| Socket                              | LED modul           |
| terminal block                      | snap terminal block |
| Automatic circuit breaker type B10A | 22 pcs              |
| Automatic circuit breaker type B16A | 36 pcs              |

## Luminous

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 2480 lm      |
| Lum. flux of light source   | 3700 lm      |
| Luminaire efficacy          | 107 lm/W     |
| Temperature                 | 2700-6500 K  |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |

Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).




Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728095802        |
| Weight NTTO       | 4.2 Kg               |
| Weight BTTO       | 4.6 Kg               |
| Number of cartons | 1 pcs                |
| Package volume    | 0.033 m <sup>3</sup> |
| Package 1 width   | 0.43 m               |
| Package 1 length  | 0.43 m               |
| Package 1 height  | 0.18 m               |
| Warranty*         | 60 months            |


\*The warranty for the batteries is valid for 12 months from the date of purchase.

Installation dimensions:



Additional assortment:

Lampshade

| Product code | Name | Color | Description | Picture  | Drawing |
|--------------|------|-------|-------------|--|---------|
| 20083        | 029  | white |             |  |         |