



ERIS C3

LED-1L16E500K88/413C HF 3K#


WWW.OSMONT.CZ

ERIS C3

Product code: ERI67038



Type: LED-1L16E500K88/413C HF 3K#

Short description of the luminaire: White surface-mounted LED light with sensor with TRIPLEX OPAL glass shade with black decorative stripe.



Technical

| | |
|------------------------------|--------------------------------|
| Types of luminaires | Sensor |
| Mounting type | surface mounted |
| Base material | steel |
| Shade material | three-layer glass TRIPLEX OPAL |
| Base color | white Ral9003 |
| Shade color | white - black |
| Holding the shade | folding system |
| Mounting location | ceiling/wall |
| Width | 445 mm |
| Length | 445 mm |
| Height | 130 mm |
| Diameter | ø 445 mm |
| mounting holes (diameter) | 4xø5mm |
| Installation wire (diameter) | 2xø16mm |
| Energy Class | D |
| Impact strength | IK01 |
| Operating temperature | from -20°C to +30°C |




Electric

| | |
|-------------------------------------|---------------------|
| Power consumption | 24 W |
| Ingress Protection | IP43 |
| Socket | LED modul |
| Sensor | HF |
| terminal block | snap terminal block |
| Automatic circuit breaker type B10A | 37 pcs |
| Automatic circuit breaker type B16A | 59 pcs |
| Automatic circuit breaker type C10A | 37 pcs |
| Automatic circuit breaker type C16A | 59 pcs |

Luminous

| | |
|-----------------------------|--------------|
| Lum. flux of luminaire | 1880 lm |
| Lum. flux of light source | 3750 lm |
| Luminaire efficacy | 78 lm/W |
| Temperature | 3000 K |
| Rated life time LED L80/B10 | 100000 hours |
| CRI | Ra80 |
| MacAdam | 3 |
| Blue light hazard | Risk group 0 |




Eulum data for calculation programs are available at

Logistic

| | |
|-------------------|----------------------|
| EAN | 8591728099213 |
| Weight NTT0 | 5.65 Kg |
| Weight BTTO | 6.15 Kg |
| Number of cartons | 1 pcs |
| Package volume | 0.033 m ³ |
| Package 1 width | 0.46 m |
| Package 1 length | 0.45 m |
| Package 1 height | 0.16 m |
| Warranty* | 60 months |


**The warranty for the batteries is valid for 12 months from the date of purchase.*

Installation dimensions:



Additional assortment:

Lampshade

| Product code | Name | Color | Description | Picture | Drawing |
|--------------|------|---------------|-------------|--|---------|
| 20132 | 413C | white - black | |  | |