



IRIDA 3

LED-1L15ET500BD14/PC64 DALI 27-65K#

WWW.OSMONT.CZ

IRIDA 3

Product code: IRI72792



Type: LED-1L15ET500BD14/PC64 DALI 27-65K#

Short description of the luminaire: White surface-mounted LED light with Tunable White system and polycarbonate shade



Technical

Types of luminaires	Tunable White
Mounting type	surface mounted
Base material	polypropylene composite
Shade material	opal polycarbonate
Base color	white Ra9003
Shade color	white
Holding the shade	bayonet
Mounting location	ceiling/wall
Width	317 mm
Length	317 mm
Height	78 mm
Diameter	ø 317 mm
mounting holes (diameter)	3xø5mm
Installation wire (diameter)	2xø16mm
Energy Class	D
Impact strength	IK10
Operating temperature	from -20°C to +30°C




Electric

Power consumption	18 W
Ingress Protection	IP65
Socket	LED modul
terminal block	snap terminal block
Automatic circuit breaker type B10A	22 pcs
Automatic circuit breaker type B16A	36 pcs

Luminous

Lum. flux of luminaire	2020 lm
Lum. flux of light source	2970 lm
Luminaire efficacy	112 lm/W
Temperature	2700-6500 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0




Eulum data for calculation programs are available at www.osmont.cz.

Logistic

EAN	8591728138417
Weight NTTO	0.75 Kg
Weight BTTO	0.95 Kg
Number of cartons	1 pcs
Package volume	0.012 m ³
Package 1 width	0.325 m
Package 1 length	0.325 m
Package 1 height	0.11 m
Warranty*	60 months

*The warranty for the batteries is valid for 12 months from the date of purchase.

Installation dimensions:



Additional assortment:

Lampshade

Product code	Name	Color	Description	Picture	Drawing
20612	PC64	white		