



## ISIS L2 PM-M HP

LED-5L06E700ZL11/PM2M/L100 C DALI 3K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

## ISIS L2 PM-M HP

Product code: ISI75203

Type: LED-5L06E700ZL11/PM2M/L100 C DALI 3K#

Short description of the luminaire: Black colour | pendant high-power LED light DALI | matt PMMA shade| steel wire pendant ( with supply cable) 100 cm |

### Technical data

|                           |                              |
|---------------------------|------------------------------|
| Types of luminaires       | Dimmable                     |
| Mounting type             | Suspended - wire             |
| Base material             | steel                        |
| Shade material            | opal polymethyl methacrylate |
| Base color                | black Ral9005                |
| Shade color               | white                        |
| Holding the shade         | steel holder                 |
| Mounting location         | ceiling                      |
| Width                     | 300 mm                       |
| Length                    | 300 mm                       |
| Height                    | 300 mm                       |
| Diameter                  | ø 300 mm                     |
| Suspension length         | 1000 mm                      |
| mounting holes (diameter) | 3xø5mm                       |
| Cable entrance            | 2xø16mm                      |
| Energy Class              | D                            |
| Impact strength           | IK06                         |
| Operating temperature     | from -20°C to +30°C          |

### Electrical data

|                                     |                     |
|-------------------------------------|---------------------|
| Power consumption                   | 33 W                |
| Ingress Protection                  | IP40                |
| Socket                              | LED modul           |
| terminal block                      | snap terminal block |
| Automatic circuit breaker type B10A | 31 pcs              |
| Automatic circuit breaker type B16A | 50 pcs              |
| Automatic circuit breaker type C10A | 52 pcs              |
| Automatic circuit breaker type C16A | 85 pcs              |
| Switching current                   | 5 A / 50 µsec       |
| Number of LED drivers               | 1                   |

### Luminous data

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 4400 lm      |
| Lum. flux of light source   | 5000 lm      |
| Luminaire efficacy          | 133 lm/W     |
| Chromaticity temperature    | 3000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |



## TECHNICAL SHEET

Full data for calculation programs are available at  
[www.osmont.cz](http://www.osmont.cz).



### Logistical data

|                   |               |
|-------------------|---------------|
| EAN               | 8591728225391 |
| Number of cartons | 2 pcs         |
| Warranty*         | 60 months     |

\*The warranty for the batteries is valid for 36 months from the date of purchase.

### Installation dimensions:



## Additional assortment:

## Lampshade

| Product code | Name         | Color | Picture                                                                           | Drawing |
|--------------|--------------|-------|-----------------------------------------------------------------------------------|---------|
| 20600        | PM2M (300mm) | white |  |         |