



## ISIS L3 PE

---

LED-5L06E600ZL11/PE3/L100 NB 4K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS L3 PE

Product code: IS166699

Type: LED-5L06E600ZL11/PE3/L100 NB 4K#

Short description of the luminaire: Stainless brushed pendant LED light ON/OFF and polyethylene shade.



## Technical

|                              |                         |
|------------------------------|-------------------------|
| Types of luminaires          | Classic on/off          |
| Mounting type                | Suspended - wire        |
| Base material                | stainless steel steel   |
| Shade material               | polyethylene            |
| Base color                   | brushed stainless steel |
| Shade color                  | white                   |
| Holding the shade            | folding system          |
| Mounting location            | ceiling                 |
| Width                        | 400 mm                  |
| Length                       | 400 mm                  |
| Height                       | 400 mm                  |
| Diameter                     | ø 400 mm                |
| Hinge length                 | 1000 mm                 |
| mounting holes (diameter)    | none                    |
| Installation wire (diameter) | none                    |
| Energy Class                 | D                       |
| Impact strength              | IK10                    |
| Operating temperature        | from -20°C to +30°C     |




## Electric

|                                     |           |
|-------------------------------------|-----------|
| Power consumption                   | 27 W      |
| Ingress Protection                  | IP40      |
| Socket                              | LED modul |
| terminal block                      | none      |
| Automatic circuit breaker type B10A | 31 pcs    |
| Automatic circuit breaker type B16A | 50 pcs    |
| Automatic circuit breaker type C10A | 52 pcs    |
| Automatic circuit breaker type C16A | 85 pcs    |

## Luminous

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 4070 lm      |
| Lum. flux of light source   | 4630 lm      |
| Luminaire efficacy          | 150 lm/W     |
| Temperature                 | 4000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |



Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).

## TECHNICAL SHEET




### Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728037703        |
| Weight NTTO       | 3.4 Kg               |
| Weight BTTO       | 4.1 Kg               |
| Number of cartons | 2 pcs                |
| Package volume    | 0.072 m <sup>3</sup> |
| Package 1 width   | 0.405 m              |
| Package 1 length  | 0.405 m              |
| Package 1 height  | 0.41 m               |
| Warranty*         | 60 months            |

*\*The warranty for the batteries is valid for 12 months from the date of purchase.*

### Additional assortment:

#### Lampshade

| Product code | Name | Color | Description | Picture  | Drawing |
|--------------|------|-------|-------------|--|---------|
| 20530        | PE3  | white |             |  |         |