



## ISIS P1 PM

---

LED-5L05E500Z11/PM1/a3 NL DALI 3K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS P1 PM

Product code: ISI72357

Type: LED-5L05E500Z11/PM1/a3 NL DALI 3K#

Short description of the luminaire: Stainless polished finish | pendant LED light | dimmable DALI | PMMA shade



## Technical

Types of luminaires	Dimmable
Mounting type	Suspended - rod
Base material	stainless steel steel
Shade material	glossy polymethyl methacrylate
Base color	polished stainless steel
Shade color	white
Holding the shade	steel holder
Mounting location	ceiling
Width	200 mm
Length	200 mm
Height	200 mm
Diameter	ø 200 mm
Hinge length	600 mm
mounting holes (diameter)	none
Installation wire (diameter)	none
Energy Class	D
Impact strength	IK06
Operating temperature	from -20°C to +30°C


## Electric

Power consumption	8 W
Ingress Protection	IP40
Socket	LED modul
terminal block	none
Automatic circuit breaker type B16A	45 pcs
Automatic circuit breaker type C16A	70 pcs

## Luminous

Lum. flux of luminaire	1080 lm
Lum. flux of light source	1230 lm
Luminaire efficacy	135 lm/W
Temperature	3000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).



Logistic

EAN	8591728046491
Weight NTTO	1.3 Kg
Weight BTTO	1.9 Kg
Number of cartons	2 pcs
Package volume	0.02 m <sup>3</sup>
Package 1 width	0.21 m
Package 1 length	0.21 m
Package 1 height	0.205 m
Warranty*	60 months

*\*The warranty for the batteries is valid for 12 months from the date of purchase.*

Additional assortment:

Lampshade

Product code	Name	Color	Description	Picture	Drawing
20622	PM1	white		