



## ISIS P2A PM-M

LED-5L06E300Z11/PM2AM/L80 NB DALI 4K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS P2A PM-M

Product code: ISI70973

Type: LED-5L06E300Z11/PM2AM/L80 NB DALI 4K#

Short description of the luminaire: Stainless steel brushed | pendant LED light DALI | matt PMMA shadel rod pendant 80 cm |



## Technical data


|                           |                              |
|---------------------------|------------------------------|
| Types of luminaires       | Dimmable                     |
| Mounting type             | Suspended - rod              |
| Base material             | stainless steel steel        |
| Shade material            | opal polymethyl methacrylate |
| Base color                | brushed stainless steel      |
| Shade color               | white                        |
| Holding the shade         | steel holder                 |
| Mounting location         | ceiling                      |
| Width                     | 250 mm                       |
| Length                    | 250 mm                       |
| Height                    | 250 mm                       |
| Diameter                  | ø 250 mm                     |
| Suspension length         | 800 mm                       |
| mounting holes (diameter) | none                         |
| Energy Class              | D                            |
| Impact strength           | IK06                         |
| Operating temperature     | from -20°C to +30°C          |

## Electrical data

|                                     |                   |
|-------------------------------------|-------------------|
| Power consumption                   | 14 W              |
| Ingress Protection                  | IP40              |
| Socket                              | LED modul         |
| terminal block                      | none              |
| Automatic circuit breaker type B10A | 41 pcs            |
| Automatic circuit breaker type B16A | 66 pcs            |
| Automatic circuit breaker type C10A | 66 pcs            |
| Automatic circuit breaker type C16A | 106 pcs           |
| Switching current                   | ≤ 7,5 A / 16 µsec |
| Number of LED drivers               | 1                 |

## Luminous data

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 2090 lm      |
| Lum. flux of light source   | 2380 lm      |
| Luminaire efficacy          | 149 lm/W     |
| Chromaticity temperature    | 4000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |



Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).

OSMONT, s.r.o.  
HYBRÁLEC 129,  
586 01 JIHLAVA, CZ

## TECHNICAL SHEET



### Logistical data

|           |               |
|-----------|---------------|
| EAN       | 8591728213534 |
| Warranty* | 60 months     |

*\*The warranty for the batteries is valid for 36 months from the date of purchase.*

### Additional assortment:

#### Lampshade

| Product code | Name          | Color | Picture   | Drawing |
|--------------|---------------|-------|---|---------|
| 20725        | PM2AM (250mm) | white |  |         |