



ISIS P4 PE

LED-5L07E900Z11/PE4/a3/NK1W NB 3K##

WWW.OSMONT.CZ

ISIS P4 PE

Product code: ISI66157

Type: LED-5L07E900Z11/PE4/a3/NK1W NB 3K##

Short description of the luminaire: Stainless brushed pendant LED light with emergency unit combined and polyethylene shade.



Technical


Types of luminaires	Emergency combined
Mounting type	Suspended - rod
Base material	stainless steel steel
Shade material	polyethylene
Base color	brushed stainless steel
Shade color	white
Holding the shade	folding system
Mounting location	ceiling
Width	500 mm
Length	500 mm
Height	500 mm
Diameter	ø 500 mm
Hinge length	600 mm
mounting holes (diameter)	none
Installation wire (diameter)	none
Energy Class	D
Impact strength	IK10
Operating temperature	from 0°C to +30°C

Electric

Power consumption	41 W
Ingress Protection	IP40
Socket	LED modul
Battery type	NiCd
Emergency time	3 hours
terminal block	none
Automatic circuit breaker type B10A	25 pcs
Automatic circuit breaker type B16A	43 pcs
Automatic circuit breaker type C10A	29 pcs
Automatic circuit breaker type C16A	52 pcs

Luminous

Lum. flux of luminaire	5870 lm
Lum. flux of light source	6670 lm
Lum. flux of light source in emergency mode	150 lm
Luminaire efficacy	143 lm/W
Temperature	3000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



TECHNICAL SHEET



Eulum data for calculation programs are available at
www.osmont.cz.

Logistic

EAN	8591728035570
Weight NTTO	4.4 Kg
Weight BTTO	6.3 Kg
Number of cartons	2 pcs
Package volume	0.171 m ³
Package 1 width	0.52 m
Package 1 length	0.52 m
Package 1 height	0.53 m
Warranty*	60 months

*The warranty for the batteries is valid for 12 months from the date of purchase.

Additional assortment:

Lampshade

Product code	Name	Color	Description	Picture	Drawing
20531	PE4	white		