



ISIS P4 PM-M

LED-5L07E900Z11/PM4M/a1 MS DALI 4K##

WWW.OSMONT.CZ

ISIS P4 PM-M

Product code: ISI70535

Type: LED-5L07E900Z11/PM4M/a1 MS DALI 4K##

Short description of the luminaire: Brass pendant LED light DALI and PMMA matt shade.



Technical


Types of luminaires	Dimmable
Mounting type	Suspended - rod
Base material	brass
Shade material	opal polymethyl methacrylate
Base color	polished brass
Shade color	white
Holding the shade	steel holder
Mounting location	ceiling
Width	500 mm
Length	500 mm
Height	500 mm
Diameter	ø 500 mm
Hinge length	200 mm
mounting holes (diameter)	none
Installation wire (diameter)	none
Energy Class	D
Impact strength	IK06
Operating temperature	from -20°C to +30°C

Electric

Power consumption	41 W
Ingress Protection	IP40
Socket	LED modul
terminal block	none
Automatic circuit breaker type B10A	14 pcs
Automatic circuit breaker type B16A	23 pcs
Automatic circuit breaker type C10A	23 pcs
Automatic circuit breaker type C16A	38 pcs

Luminous

Lum. flux of luminaire	6120 lm
Lum. flux of light source	6960 lm
Luminaire efficacy	149 lm/W
Temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0



Eulum data for calculation programs are available at www.osmont.cz.

Logistic

EAN	8591728042127
Weight NTTO	4.4 Kg
Weight BTTO	6.3 Kg
Number of cartons	2 pcs
Package volume	0.157 m ³
Package 1 width	0.52 m
Package 1 length	0.52 m
Package 1 height	0.53 m
Warranty*	60 months

**The warranty for the batteries is valid for 12 months from the date of purchase.*

Additional assortment:

Lampshade

Product code	Name	Color	Description	Picture	Drawing
20604	PM4-M	white			