



ISIS P5 PM

LED-5L07E1050Z11/PM5/a3 C 4K##

WWW.OSMONT.CZ

ISIS P5 PM

Product code: ISI60512

Type: LED-5L07E1050Z11/PM5/a3 C 4K##

Short description of the luminaire: Black color | pendant LED light | ON/OFF | PMMA shade



Technical

Types of luminaires	Classic on/off
Mounting type	Suspended - rod
Base material	steel
Shade material	glossy polymethyl methacrylate
Base color	black Ral9005
Shade color	white
Holding the shade	steel holder
Mounting location	ceiling
Width	600 mm
Length	600 mm
Height	600 mm
Diameter	ø 600 mm
Hinge length	600 mm
mounting holes (diameter)	none
Installation wire (diameter)	none
Energy Class	D
Impact strength	IK06
Operating temperature	from -20°C to +30°C



Electric

Power consumption	48 W
Ingress Protection	IP40
Socket	LED modul
terminal block	none

Luminous

Lum. flux of luminaire	7100 lm
Lum. flux of light source	8070 lm
Luminaire efficacy	147 lm/W
Temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at www.osmont.cz.



TECHNICAL SHEET



Logistic

EAN	8591728014742
Weight NTTO	5.4 Kg
Weight BTTO	8 Kg
Number of cartons	2 pcs
Package volume	0.278 m ³
Package 1 width	0.62 m
Package 1 length	0.62 m
Package 1 height	0.63 m
Warranty*	60 months

**The warranty for the batteries is valid for 12 months from the date of purchase.*

Additional assortment:

Lampshade

Product code	Name	Color	Description	Picture	Drawing
20666	PM5	white			