



## ISIS S3 PM-M HP

LED-5L08E850ZS11/PM3M/L100 NK3HST NL 3K#

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS S3 PM-M HP

Product code: ISI61053

Type: LED-5L08E850ZS11/PM3M/L100 NK3HST NL 3K#

Short description of the luminaire: Stainless steel polished | pendant high-power LED light with emergency backup combined (with Self-test) | matt PMMA shade| cable pendant (with inner support wire) 100 cm |



## Technical

|                           |                              |
|---------------------------|------------------------------|
| Types of luminaires       | Emergency combined SELFTEST  |
| Mounting type             | Suspended - cable            |
| Base material             | stainless steel steel        |
| Shade material            | opal polymethyl methacrylate |
| Base color                | polished stainless steel     |
| Shade color               | white                        |
| Holding the shade         | steel holder                 |
| Mounting location         | ceiling                      |
| Width                     | 400 mm                       |
| Length                    | 400 mm                       |
| Height                    | 400 mm                       |
| Hinge length              | 1000 mm                      |
| mounting holes (diameter) | 3xØ5mm                       |
| Cable entrance            | 2xØ16mm                      |
| Energy Class              | D                            |
| Impact strength           | IK06                         |
| Operating temperature     | from -20°C to +30°C          |

## Electric

|                    |                     |
|--------------------|---------------------|
| Power consumption  | 52 W                |
| Ingress Protection | IP40                |
| Socket             | LED modul           |
| Battery type       | LiFePO4             |
| Emergency time     | 3 hours             |
| SELFTEST           | yes                 |
| terminal block     | snap terminal block |

## Luminous

|   |              |
|---|--------------|
| Lum. flux of luminaire                      | 7300 lm      |
| Lum. flux of light source                   | 8290 lm      |
| Lum. flux of light source in emergency mode | 200 lm       |
| Temperature                                 | 3000 K       |
| Rated life time LED L80/B10                 | 100000 hours |
| CRI   | Ra80         |
| MacAdam                                     | 3            |
| Blue light hazard                           | Risk group 0 |

Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).



Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728156572        |
| Weight NTTO       | 3.4 Kg               |
| Weight BTTO       | 4.1 Kg               |
| Number of cartons | 2 pcs                |
| Package volume    | 0.072 m <sup>3</sup> |
| Package 1 width   | 0.405 m              |
| Package 1 length  | 0.405 m              |
| Package 1 height  | 0.41 m               |
| Warranty*         | 60 months            |

\*The warranty for the batteries is valid for 12 months from the date of purchase.

Installation dimensions:



## Additional assortment:

## Lampshade

| Product code | Name  | Color | Description   | Picture   | Drawing |
|--------------|-------|-------|---------------|---|---------|
| 20602        | PM3-M | white | příslušenství |  |         |