



## ISIS S4 PM

---

LED-5L07E900ZS11/PM4/L100 MS 3K##

[WWW.OSMONT.CZ](http://WWW.OSMONT.CZ)

# ISIS S4 PM

Product code: IS164326

Type: LED-5L07E900ZS11/PM4/L100 MS 3K##

Short description of the luminaire: Brass pendant LED light ON/OFF and PMMA shade.



## Technical



|                              |                                |
|------------------------------|--------------------------------|
| Types of luminaires          | Classic on/off                 |
| Mounting type                | Suspended - cable              |
| Base material                | brass                          |
| Shade material               | glossy polymethyl methacrylate |
| Base color                   | polished brass                 |
| Shade color                  | white                          |
| Holding the shade            | steel holder                   |
| Mounting location            | ceiling                        |
| Width                        | 500 mm                         |
| Length                       | 500 mm                         |
| Height                       | 500 mm                         |
| Diameter                     | Ø 500 mm                       |
| Hinge length                 | 1000 mm                        |
| mounting holes (diameter)    | none                           |
| Installation wire (diameter) | none                           |
| Energy Class                 | D                              |
| Impact strength              | IK06                           |
| Operating temperature        | from -20°C to +30°C            |

## Electric

|                                     |           |
|-------------------------------------|-----------|
| Power consumption                   | 41 W      |
| Ingress Protection                  | IP40      |
| Socket                              | LED modul |
| terminal block                      | none      |
| Automatic circuit breaker type B10A | 35 pcs    |
| Automatic circuit breaker type B16A | 65 pcs    |
| Automatic circuit breaker type C10A | 35 pcs    |
| Automatic circuit breaker type C16A | 65 pcs    |

## Luminous

|                             |              |
|-----------------------------|--------------|
| Lum. flux of luminaire      | 5870 lm      |
| Lum. flux of light source   | 6670 lm      |
| Luminaire efficacy          | 143 lm/W     |
| Temperature                 | 3000 K       |
| Rated life time LED L80/B10 | 100000 hours |
| CRI                         | Ra80         |
| MacAdam                     | 3            |
| Blue light hazard           | Risk group 0 |



Eulum data for calculation programs are available at [www.osmont.cz](http://www.osmont.cz).

Logistic

|                   |                      |
|-------------------|----------------------|
| EAN               | 8591728028466        |
| Weight NTTO       | 3.8 Kg               |
| Weight BTTO       | 5.3 Kg               |
| Number of cartons | 2 pcs                |
| Package volume    | 0.148 m <sup>3</sup> |
| Package 1 width   | 0.52 m               |
| Package 1 length  | 0.52 m               |
| Package 1 height  | 0.53 m               |
| Warranty*         | 60 months            |

*\*The warranty for the batteries is valid for 12 months from the date of purchase.*

Additional assortment:

Lampshade

| Product code | Name | Color | Description | Picture  | Drawing |
|--------------|------|-------|-------------|--|---------|
| 20603        | PM4  | white |             |  |         |