



KRUGER 4 F0

LED-6L51EMP700KN10/F04C NK3HST 4K##

WWW.OSMONT.CZ

KRUGER 4 FO

Product code: KRU50520

Type: LED-6L51EMP700KN10/FO4C NK3HST 4K##

Short description of the luminaire: Black colour | ceiling or wall LED light with emergency backup combined (with Self-test) | multipower driver | opal plastic shade| decorative collar | |



Technical data

Types of luminaires	Emergency combined SELFTEST
Mounting type	surface mounted
Base material	steel
Shade material	Plastic opal (FO) with metal collar
Base color	black Ral9005
Shade color	white - black
Holding the shade	folding system
Mounting location	ceiling/wall
Width	645 mm
Length	645 mm
Height	80 mm
Diameter	ø 645 mm
mounting holes (diameter)	2xø5mm
Cable entrance	2xø16mm
Energy Class	D
Operating temperature	from -20°C to +30°C




Electrical data

Power consumption	65 W
Ingress Protection	IP40
Socket	LED modul
Battery type	LiFePO4
Emergency time	3 hours
SELFTEST	yes
terminal block	snap terminal block

Luminous data

Lum. flux of luminaire	7800 lm
Lum. flux of light source	10980 lm
Lum. flux of light source in emergency mode	200 lm
Chromaticity temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at www.osmont.cz.



TECHNICAL SHEET




Logistical data

EAN	8591728229795
Number of cartons	1 pcs
Warranty*	60 months

*The warranty for the batteries is valid for 36 months from the date of purchase.

Installation dimensions:



Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20730	F04C	white - black	