



MATAR 2

LED-1L78-1L79E400PA09/PC72 B 3/35/4K##

WWW.OSMONT.CZ

MATAR 2

Product code: MAT71586

Type: LED-1L78-1L79E400PA09/PC72 B 3/35/4K##

Short description of the luminaire: White colour | ceiling or wall LED light ON/OFF | opal polycarbonate shade (PC)



Technical data

Types of luminaires	Classic on/off
Mounting type	surface mounted
Base material	aluminium
Shade material	opal polycarbonate
Base color	white Ral9003
Shade color	white
Holding the shade	spring
Mounting location	ceiling/wall
Width	905 mm
Length	58 mm
Height	46 mm
mounting holes (diameter)	2xØ5mm
Cable entrance	2xØ16mm
Energy Class	D
Impact strength	IK10
Operating temperature	from -20°C to +30°C





Electrical data

Power consumption	15 W
Ingress Protection	IP44
Socket	LED modul
terminal block	snap terminal block

Luminous data

Lum. flux of luminaire	1740/1820 lm
Lum. flux of light source	2460/2560 lm
Chromaticity temperature	3000/3500/4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at www.osmont.cz.



Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20609	PC72	white	