



STYX D1

Private: LED-5L05E600BD1P/192 MS 3K#

WWW.OSMONT.CZ

STYX D1

Product code: STY61254

Type: Private: LED-5L05E600BD1P/192 MS 3K#



Technical data

Types of luminaires	Classic on/off
Mounting type	surface mounted
Base material	brass
Shade material	three-layer glass TRIPLEX OPAL
Base color	polished brass
Shade color	white
Holding the shade	bayonet
Mounting location	ceiling/wall
Width	200 mm
Length	200 mm
Height	185 mm
Diameter	Ø 200 mm
mounting holes (diameter)	4x?5mm
Cable entrance	2x?16mm
Impact strength	IK01
Operating temperature	from -20°C to +30°C




Electrical data

Power consumption	10 W
Ingress Protection	IP65
Socket	LED modul
terminal block	screw terminal block

Luminous data

Lum. flux of luminaire	1280 lm
Lum. flux of light source	1460 lm
Chromaticity temperature	3000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0




Eulum data for calculation programs are available at www.osmont.cz.

Logistical data

EAN	8591728231590
Number of cartons	1 pcs
Warranty*	60 months

*The warranty for the batteries is valid for 36 months from the date of purchase.

Installation dimensions:



Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20092	192	white		