



SUBRA 1

LED-6L71E350N1/PM811 B 3K##

WWW.OSMONT.CZ

SUBRA 1

Product code: SUB60024

Type: LED-6L71E350N1/PM811 B 3K##

Short description of the luminaire: White colour | ceiling or wall LED light ON/OFF | matt PMMA shade



Technical data

Types of luminaires	Classic on/off
Mounting type	surface mounted
Base material	steel
Shade material	opal polymethyl methacrylate
Base color	white Ra9003
Shade color	white
Holding the shade	screws
Mounting location	ceiling
Width	50 mm
Length	80 mm
Height	513 mm
mounting holes (diameter)	2xØ5mm
Cable entrance	2xØ16mm
Energy Class	C
Impact strength	IK04
Operating temperature	from -20°C to +30°C



Electrical data

Power consumption	12 W
Ingress Protection	IP20
Socket	LED modul
terminal block	snap terminal block

Luminous data

Lum. flux of luminaire	1650 lm
Lum. flux of light source	2110 lm
Chromaticity temperature	3000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at www.osmont.cz.



TECHNICAL SHEET




Logistical data

EAN	8591728232351
Number of cartons	1 pcs
Warranty*	60 months

**The warranty for the batteries is valid for 36 months from the date of purchase.*

Installation dimensions:



Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20734	PM811 (pr.50/513mm)	white	