OSMONT®

ELISA

LED-1L43E1050NU43/PC43 HF 3K#

WWW.OSMONT.CZ

ELISA

Product code: ELI56397

Type: LED-1L43E1050NU43/PC43 HF 3K#

Short description of the luminaire: White colour | ceiling or wall LED light with HF sensor | opal polycarbonate shade (PC)|

Technical data

Types of luminaires	Sensor
Mounting type	surface mounted
Base material	steel
Shade material	opal polycarbonate
Base color	white Ral9003
Shade color	white
Holding the shade	folding system
Mounting location	wall
Width	490 mm
Length	265 mm
Height	85 mm
mounting holes (diameter)	3xØ5mm
Cable entrance	2xØ16mm
Energy Class	D
Impact strength	IK10
Operating temperature	from -20°C to +30°C



Electrical data

Power consumption	26 W
Ingress Protection	IP44
Socket	LED modul
Sensor	HF
terminal block	snap terminal block
Automatic circuit breaker type B10A	24 pcs
Automatic circuit breaker type B16A	40 pcs
Automatic circuit breaker type C10A	24 pcs
Automatic circuit breaker type C16A	40 pcs
Switching current	20 A / 90 µsec
Number of LED drivers	1



Luminous data

Lum. flux of luminaire	2790 lm
Lum. flux of light source	4110 lm
Luminaire efficacy	107 lm/W
Chromaticity temperature	3000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

Eulum data for calculation programs are available at www.osmont.cz.

OSMONT, s.r.o.
HYBRÁLEC 129,
586 01 JIHLAVA, CZ

www.osmont.cz
osmont@osmont.cz
(+420) 567 210 023

Logistical data

EAN	8591728095215
Weight NTTO	1.69 Kg
Weight BTTO	2 Kg
Number of cartons	1 pcs
Package volume	0.016 m^3
Package 1 width	0.41 m
Package 1 length	0.41 m
Package 1 height	0.09 m
Warranty*	60 months

**The warranty for the batteries is valid for 36 months from the date of purchase.*

Installation dimensions:



Additional assortment:

Lampshade

Product code	Name	Color	Picture	Drawing
20537	PC43	white		