ELSA 5

LED-1L19E500BT16/626 HF 4K##

WWW.OSMONT.CZ

ELSA 5

Product code: ELS68585

Type: LED-1L19E500BT16/626 HF 4K##

Short description of the luminaire: White colour | ceiling or wall LED light with HF sensor | TRIPLEX OPAL hand blown glass shade|



Technical data

Types of luminaires	Sensor
Mounting type	surface mounted
Base material	steel
Shade material	three-layer glass TRIPLEX OPAL
Base color	white Ral9003
Shade color	white
Holding the shade	bayonet
Mounting location	ceiling/wall
Width	500 mm
Length	500 mm
Height	92 mm
Diameter	ø 500 mm
mounting holes (diameter)	3xØ5mm
Cable entrance	2xØ16mm
Energy Class	D
Impact strength	IK01
Operating temperature	from -20°C to +30°C



Electrical data

Power consumption	26 W
Ingress Protection	IP44
Socket	LED modul
Sensor	HF
terminal block	snap terminal block
Automatic circuit breaker type B10A	37 pcs
Automatic circuit breaker type B16A	59 pcs
Automatic circuit breaker type C10A	37 pcs
Automatic circuit breaker type C16A	59 pcs
Switching current	15 A / 100 µsec
Number of LED drivers	1



Luminous data

Lum. flux of luminaire	2730 lm
Lum. flux of light source	4200 lm
Luminaire efficacy	105 lm/W
Chromaticity temperature	4000 K
Rated life time LED L80/B10	100000 hours
CRI	Ra80
MacAdam	3
Blue light hazard	Risk group 0

OSMONT, s.r.o.
HYBRÁLEC 129,
586 01 JIHLAVA, CZ

www.osmont.cz
osmont@osmont.cz
(+420) 567 210 023

Eulum data for calculation programs are available at www.osmont.cz.

Logistical data

EAN	8591728096762
Weight NTTO	6.9 Kg
Weight BTTO	7.4 Kg
Number of cartons	1 pcs
Package volume	0.034 m^3
Package 1 width	0.49 m
Package 1 length	0.49 m
Package 1 height	0.14 m
Warranty*	60 months

**The warranty for the batteries is valid for 36 months from the date of purchase.*

Installation dimensions:



Additional assortment:

Base for surface mounting

Product code	Name	Color	Picture	Drawing
33509	B16/BP 2-1 B	white Ral9003		

Lampshade

Product code	Name	Color	Picture	Drawing
20103	626	white		

OSMONT, s.r.o.
HYBRÁLEC 129,
586 01 JIHLAVA, CZ

www.osmont.cz
osmont@osmont.cz
(+420) 567 210 023